



LAUNCH

CAT-501 + Auto Transmission Cleaner Changer

The transmission fluid inside auto transmissions will deteriorate over time and if the transmission fluid is not changed in time, it may cause abnormal wear to the transmission.

The Launch transmission fluid changer can precisely control the filling/extraction quantity of the ATF as required. The extracted amount is measured and new fluid is precisely metered into the transmission. The **CAT-501 auto transmission fluid changer** can complete the flush and fluid exchange in 20 minutes for transmission, torque converter and radiator. The fluid exchange rate is nearly 100%.

- **LCD display and compact design makes operation easy and intuitive.**
- **Automatic filling of automatic transmission fluid with 100ml increments.**
- **Automatic identification of the power polarity.**
- **Automatic selects the fluid flow in and out direction.**
- **Automatic circulation cleaning function of automatic transmission.**
- **Automatic exchange of new/used fluid.**
- **Visual display the fluid pressure of A/F radiator and the fluid outlet pressure of the unit.**

BACKED up by **AECS** product support.
Service and calibrate the equipment by including it on our annual calibration run.



SPECIFICATIONS

Power supply: AC110V, 220V ± 10% 50Hz~ 60Hz
Equivalent exchange error: ±100ml
Max Detergent capacity: 1000ml
Temperature sensitivity: ± 1 °C
Filter precision: 5µm
Noise: <70db
Pump consumption: 150W
Dimensions: 700*700*1300mm(L * W * H)
Ambient temperature: -10~+40°C
Relative humidity: <85%