

Model : **Tyremate 200 TL - RFT**

Model : **Tyremate 200 TL**

Model : **TC - XL - 40**



» Fully Automatic - Run Flat Tyre «

- Suitable for Car and LCV tyres
- Pneumatically operated tilting type vertical column
- Pneumatically operated twin cylinders for firm clamping
- Four Jaw self centering chuck
- Alloy wheel plastic protector for jaws
- Capable of handling stiff, wide and low-profile tyre
- Right help arm

» Fully Automatic Tubeless «

- Suitable for Car and LCV tyres
- Pneumatically operated tilting type vertical column
- Pneumatically operated twin cylinders for firm clamping
- Four Jaw self centering chuck
- Alloy wheel plastic protector for jaws

» Semi Automatic «

- Suitable for Car and LCV tyres
- Wheel Rim size 10" - 21"
- Pneumatically operated twin cylinders for firm clamping
- Four Jaw self centering chuck
- Alloy wheel plastic protector

Technical Specification

Technical Specification	Tyremate 200 TL - RFT Tyremate 200 TL	TC - XL - 40
Rim clamping from inside	12" – 24" (305 – 610 mm)	12" – 21" (305 – 533 mm)
Rim clamping from outside	10" – 20" (254 – 508 mm)	10" – 18" (254 – 457 mm)
Max. wheel diameter	41" (1041 mm)	37" (930 mm)
Max. wheel width	3" - 12" (76 - 305 mm)	3" - 12" (76 - 305 mm)
Operating pressure	6 – 8 bar	6 – 8 bar
Bead breaker force	2500 kg	2500 kg
Power supply	220 - 240V AC, Single Phase, 50Hz	220 - 240V AC, Single Phase, 50Hz
Power	1.5 HP	1.5 HP

Standard Accessories



Optional Accessories

